Platinum Series

Single Full Metal Bed



*shown with optional mattress

Bed Construction

- Will not fracture under a bend test
- Free from rust, scale, pits, scratches, and buckles
- **35% recycled content**
- Posts constructed of 1.5" square weld seam tubing
- Panels constructed of rolled sheet metal with reinforced inserts
- Capped posts and 1" square cross tube
- Floor to bed clearance of 13" in middle and 10" on ends
- Double hook locks
- No exposed raw metal edges
- Multi-welded for durability and long-lasting service

Finish/Paint

- Top quality powder coating
- All surfaces cleaned and degreased for optimum paint adhesion
- Paint hardened by baking at 325 degrees Fahrenheit for 20 minutes

Spring Base Construction

- Side rails are 2" x 1.5" x 5/32 rail steel with a 2" flange
- End angles are 2" x 1.5" x 5/32 rail steel angle with a 1.5" flange
- **Spring base converts from 75" length to XL 80" length**
- All corners fitted with shoulder rivets to fit double hook locks
- Contains 15 stands of "Z" hook springs
- Springs connected by 4 rows of carbon wire
- **Sleep surface rated for intense use up to 400 lbs**



Sturdy spring base sleep surface rated for use up to 400 lbs.



Spring base adjusts length.

Contact us: 1.800.203.2507 sales@americanbeddingmfg.com