AMERICAN BEDDING
MANUFACTURERS, Inc.
americanbeddingmfg.com

Platinum Series

Single Metal Bed

	Sleep Surface	Overall Dimensions	Weight
PL-360S-750/800:	36" W 75"/80" L 13" H	36" W 78"/84" L 29.5" H	164 lbs
PL-380S-750/800:	38" W 75"/80" L 13" H	38" W 78"/84" L 29.5" H	172 lbs



*shown with optional nightstand and underbed chest

Finish/Paint

- Top quality powder coating
- All surfaces cleaned and degreased for optimum paint adhesion
- Paint hardened by baking at 325 degrees Fahrenheit for 20 minutes

Spring Base Construction

- Side rails are 2" x 1.5" x 5/32 rail steel with a 2" flange
- End angles are 2" x 1.5" x 5/32 rail steel angle with a 1.5" flange
- **Spring base converts from 75" length to XL 80" length**
- All corners fitted with shoulder rivets to fit double hook locks
- Contains 15 stands of "Z" hook springs
- Springs connected by 4 rows of carbon wire
- **Sleep surface rated for intense use up to 400 lbs**

Bed Construction

- Will not fracture under a bend test
- Free from rust, scale, pits, scratches, and buckles
- **Demountable design**
- **35% recycled content**
- Posts constructed of 1.5" square weld seam tubing
- Panels constructed of rolled sheet metal with reinforced inserts
- Capped posts and 1" square cross tube
- Floor to bed clearance of 13" in middle and 10" on ends
- Double hook locks
- No exposed raw metal edges
- Multi-welded for durability and long-lasting service



Spring base adjusts length.



Also available in Full sizes.

Contact us: 1.800.203.2507 sales@americanbeddingmfg.com